


Tapped
Density

TD 1

Compact tester that combines two USP / Ph. Eur. methods in one instrument. Print test protocols and connect your external analytical balance for automated data transfer.

SOTAX



Tapped Density Tester



TD1 — Compact. Versatile. Compliant.



sotax.com/TD1

Suitable for different
cylinder sizes / volumes

Quick-change between
different stroke heights for
USP / Ph.Eur. methods 1 and 2

Menu-guided qualification
procedure with printed report

Test protocols including Tapped
Density, Compressibility Index,
and Hausner Ratio

Networking and data
management with q-doc®



User-friendly SingleButton™
navigation

Recording of weight readings from
external analytical balance



Two test methods in
one instrument

USP, Ph. Eur., ASTM, and
DIN EN ISO compliant

Print test protocols

Password protection

Small footprint



Simply versatile.

The TD1 combines two USP / Ph. Eur. test methods with different stroke heights into one compact single station instrument. Its unique quick-change holder accepts various cylinder sizes – making it the ideal tester for both routine and research tasks. Starting test sequences is fast and easy with SingleButton™ navigation.


100% compliance.

Robust in design, the TD1 fully complies with all applicable norms and standards for tapped density testing of powders – including Pharmacopeia, ASTM, and DIN EN ISO. Qualification intervals can be set as required by your internal procedures. To ensure standardized execution, the qualification routine is fully menu-guided.

Report results as needed.

To document testing sequences, the TD1 features built-in reporting capabilities. Test protocols with automatic calculation of Tapped Density, Compressibility Index, and Hausner Ratio can be printed on completion of a test. If needed, the TD1 can also be integrated with q-doc® data management for consolidated batch reporting of various tests performed on different instruments.

Example:
q-doc® network with TD1



TD1 Technical Specifications

Number of stations	1	
Test methods	USP <616> / Ph. Eur. 2.9.34, Method 1	●
	USP <616> / Ph. Eur. 2.9.34, Method 2	●
	ASTM B 527	●
	DIN EN ISO 787-11	●
	DIN EN ISO 3953	●
	User-defined	●
Strokes per minute	Method 1	300
	Method 2	250
	User-defined	50 – 300, programmable
Stroke height	Method 1	14 mm, ± 2 mm
	Method 2	3 mm, ± 0.2 mm
Cylinder types	Glass cylinder, 250 mL volume	●
	Glass cylinder, 100 mL volume	●
	Glass cylinder, 25 mL volume	○
	Glass cylinder, 10 mL volume	○
Balance connection	Mettler Toledo® / Acculab®	●
User interface	Password protection	●
Printer	LAN printer / Epson® 40col.	Ethernet / RS-232 serial
Data Management	q-doc® software, for data collection	○
Interfaces	Ethernet, 2 × RS-232 serial	
Noise emission	without optional noise reduction cabinet	78 dB (A)
	with optional noise reduction cabinet	58 dB (A)
Power supply	100 – 240 V / 50 – 60 Hz	
Weight	(without packaging)	9 kg (19.8 lbs)
Dimensions	Width	230 mm (9.1 inch)
	Depth	300 mm (11.8 inch)
	Height (without glass cylinder)	270 mm (10.6 inch)
CE Conformity	The TD1 fully complies with all CE and EMC equipment guidelines relative to mechanical and electrical safety and electromagnetic compatibility.	

● included / required
○ optional

Technical specifications are subject to change without prior notice. Products illustrated in this brochure may include options or modifications not fitted as standard. No liability for errors and omissions.

SOTAX Worldwide.

Europe

Switzerland (HQ Europe)

Aesch / Basel

P Tech Support +41 61 487 5460

P Office +41 61 487 5454

info@sotax.com

Czech Republic

Prague

P Tech Support +41 61 487 5460

P Office +420 246 039 260

sotaxCZ@sotax.com

France

Saint-Louis

P Tech Support +41 61 487 5460

P Office +33 3 8970 0846

info@sotax.com

Germany

Lörrach

P Tech Support +41 61 487 5460

P Office +49 7621 16 5635

info@sotax.com

Great Britain

Foston, Derbyshire

P Tech Support +44 1332 981 571

P Office +44 1332 981 303

sotaxGB@sotax.com

Italy

Milan

P Tech Support +41 61 487 5460

P Office +39 02 8363 2641

sotaxitalia@sotax.com

Ireland

Longford, Co. Longford

P Tech Support +353 43 334 7779

P Office +353 43 334 7779

sotaxIE@sotax.com

Americas

USA (HQ Americas)

Westborough, MA

P Tech Support +1 508 544 4040

P Office +1 508 417 1112

sotaxusa@sotax.com

Canada

Westborough, MA

P Tech Support +1 508 544 4040

P Office +1 508 417 1112

sotaxcanada@sotax.com

Asia-Pacific

Thailand (HQ Asia-Pacific)

Bangkok

P Tech Support +91 99 2021 1211

P Office +66 20 02 71 15

sotaxasia@sotax.com

India

Mumbai

P Tech Support +91 99 2021 1211

P Office +91 22 2685 1903

sotaxindia@sotax.com